

Dew Point Mirror 473



Reliable Measurement

The Model 473 Dew Point Mirror is a portable instrument equipped with a separate measuring head for both spot and continuous measurement of Dew/Frost point and temperature in air and gas mixtures. Based on the chilled mirror principle, the 473 ensures direct and accurate humidity measurement.

Full Color Touch Screen

The system uses a full color active matrix liquid crystal display with an integral touch panel. It has a high contrast ratio and a wide viewing angle for easy readability. Data is displayed in large easy to read fonts. Using the on screen buttons and menus, you can easily configure each line of the display for a variety of humidity, temperature, and pressure parameters that may be viewed in either SI or non-SI units. The simple touch of a button toggles any parameter between numeric or graph format.

Remote Measuring Head

The measuring head is separate from the control/display unit for use in chambers and other environments of various humidity/ temperature ranges without the need for external heating of the gas path. A mounting kit for pipes and tubes, including flowmeter and valve, is available as an option. For measurement of environment temperature, a separate temperature sensor is either mounted on the measuring head or available as a separate remote probe with a connection to the instrument back panel.

Digital I/O

The 473 is equipped with an RS-232 digital output for recording or remote readout of the measured and calculated values.

Verifiable Calibration

Easily check the calibration at any time using the built-in Ice Test function, which provides instant verification of system integrity.

Model:	473
Measuring range:	
Frost/Dew Point	-20...+70°C
% RH	5...100%
Temperature	-50...+150°C
Accuracy:	
Frost/Dew point	±0.2°C
Temperature	±0.1°C
Reproducibility:	
Frost/Dew Point	± 0.05°C
Temperature	± 0.05°C
Thermoelectric Mirror cooling:	1-stage, 40°C depression
Cooling:	Air
Display:	Active Matrix Color Graphic LCD
Digital I/O:	RS-232
Mirror temperature sensor:	PRT-100
Operation temperature:	
Instrument	-10...+40°C
Measuring head	-20...+80°C
Storage temperature:	-10...+50°C
Ambient humidity: Instrument:	90% RH max., non condensing in operation
Voltage:	100...240 VAC, 50/60 Hz (Battery operation optional)
Power consumption:	100 Watt
Width:	310 mm (600 mm with transport case)
Height:	155 mm (310 mm with transport case)
Depth:	265 mm (450 mm with transport case)
Weight:	7 kg (17 kg with transport case)



RH Systems
11500 Signal NE, Bldg 2
Albuquerque, NM 87122
USA

Phone 505 856-5766
Fax 505 856-5866

www.rhsystems.net
info@rhsystems.net

We reserve the right to change design or technical data without notice.